Floor Decal Installation Guide

Tools for Installation



Squeege

Isopropyl Alcohol



Towel

Masking Tape



Scissors

Prepare the Surface



Be sure that your surface is clean, stable, and in good condition. Any area where you will install floor decals should be completely free of dirt. Any debris that is not cleaned up will likely be trapped underneath finished graphics.



For smooth surfaces such as tile, glass, wood, or concrete, you should saturate a lint-free towel with rubbing alcohol and wipe down the entire surface.




Allow the surface to thoroughly dry.

Install the Graphic



Position your decal onto the floor, then create a center hinge using tape, as shown in diagram **1**. Be sure to avoid any seams or grout lines.




Fold back one end of the decal, then peel the decal away from the liner, as shown in diagram 2. Now trim off the top half of the liner.



Starting at the tape, squeegee from the middle area over to one edge of the decal. Then squeegee from the middle to the other edge. Be sure to overlap your squeegee lines for maximum bonding.



shown in diagram 4.



5 Now fold back the other half of the decal and remove the liner.



6 Squeegee the other half of the decal to the surface using the same squeegee pattern, and DONE!



ARC | 833-272-8880 e-arc.com | riotcolor.com Copyright © ARC Document Solutions, LLC 2022.

ARC, ARC Document Solutions and the ARC logo are registered trademarks of ARC Document Solutions, LLC in the U.S. and/or other countries.